
"EXPRESS MAIL" MAILING LABEL NUMBER

EL 223 803 332 45

DATE OF DEPOSIT: 12-16-01

I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING
DEPOSITED WITH THE UNITED STATES POSTAL SERVICE
"EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE
UNDER 37 cfr 1.10 ON THE DATE INDICATED ABOVE AND
IS ADDRESSED TO THE COMMISSIONER OF PATENTS AND
TRADEMARKS, WASHINGTON, D.C. 20231.

MARCIA A. SNOW

TYPED OR PRINTED NAME OF PERSON MAILING

Marcia A. Snow

SIGNATURE OF PERSON MAILING PAPER OR FEE

UNITED STATES PATENT APPLICATION

FOR

BACK-FLOW VALVE AND TRIGGER FOR A CLEANING MACHINE

BEST AVAILABLE COPY

BACK-FLOW VALVE AND TRIGGER FOR A CLEANING MACHINE

BACKGROUND OF THE INVENTION:

This invention relates generally to vacuum type cleaning machines and more particularly concerns back-flow valves and valve triggers facilitating cyclical washing
5 of the cleaning machine filters.

Back flow valves typically employ gates which are directly mechanically or electrically driven. Consequently, the speed of movement of the gate is governed throughout its range of motion. The result is a response time that is detrimental to the smooth operation of the machine, the filtering action being blocked for
10 unnecessarily long intervals because of the slow response of the back-flow valve. Furthermore, these mechanical and electronic systems are extremely complex and expensive and available only on the most expensive cleaning machines. For lower priced equipment, down time for filter replacement or cleaning is required.

In one valve system disclosed in U.S. Patent No. 4,618,352 to Nelson, cams within the system air ducts rotate in direct physical contact with their valve gates, holding the gates in horizontal planes until notches in the cams allow them to rotate into diagonal planes. This system has serious power and efficiency problems. First of all, the cams are disposed on a common shaft. The common shaft arrangement of the cams requires side-by-side alignment of the system ducts transverse to the
15 common shaft. This adds to duct length and imposes location requirements which increase system losses and structural complexity. Second, the notches are angularly displaced on the cams to synchronize the operation of the gates. Since the gates are in direct contact with the cams, the notches must be relatively wide in order for the gates to open for a sufficient interval. This imposes limitations on
20 the blower to vacuum time ratios which greatly reduce the efficiency of the system. Third, in the horizontal condition the gates completely seal the openings to the blower ducts. However, in the diagonal condition only the free ends of the gates engage the vacuum ducts, so that there is no seal and air loss occurs. Fourth,

25

since the cam notches receive the gates, the cam diameters must be greater than the ducts the gates close. Consequently, for the gates and cams to maintain physical contact, the ducts must be slotted to receive the cams. Therefore, special housings are required to prevent further air losses in the system. Fifth, the cams are constantly driven so that the back-flow cycle occurs throughout the cleaning process, reducing the normal operating efficiency of the system. Sixth, because there is no seal during the vacuum process, the speed of operation of the gate is left essentially to an initial push by the blower and the force of gravity rather than taking advantage of the vacuum to help slam the gate home. Seventh, the blower and the vacuum share a common shaft, so the blower is operating unnecessarily throughout the vacuum process. The composite result of these individual problems is that the system is ineffective for cleaning at any appreciable distance from the machine.

It is, therefore, an object of this invention to provide a back-flow valve and valve trigger which facilitate cyclical washing of the cleaning machine filters. Another object of this invention is to provide a back-flow valve and valve trigger which have a rapid response time so as to limit the duration of the back flow interval. A further object of this invention is to provide a back-flow valve and valve trigger using a gate which is air-flow biased by both a blower and a vacuum source toward a back-flow condition. Yet another object of this invention is to provide a back-flow valve and valve trigger using a gate which is not mechanically controlled during its transition from normal operation to back-flow operation. It is also an object of this invention to provide a back-flow valve and valve trigger using a gate which is not electrically controlled during its transition from normal operation to a back-flow operation. Still another object of this invention is to provide a back-flow valve and valve trigger using a gate which is not governed during its transition from normal operation to back-flow operation. Another object of this invention is to provide a back-flow valve and valve trigger which do not unnecessarily increase the

length of the internal duct system. Another object of this invention is to provide a back-flow valve and valve trigger which eliminate openings and gaps which would cause pressure losses in the system. Still another object of this invention is to provide a back-flow valve and valve trigger in which an external valve trigger controls an internal valve gate. Still another object of this invention is to provide a back-flow valve and valve trigger which provide a relatively short back-flow interval during each filter cycle. Another object of this invention is to provide a back-flow valve and valve trigger which require only intermittent use of the back-flow system during the normal vacuuming process. An additional object of this invention is to provide a back-flow valve and valve trigger which are relatively simple and inexpensive. And it is an object of this invention to provide a back-flow valve and valve trigger which require operation of the blower only during the back-flow process.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2

SUMMARY OF THE INVENTION:

A valve and a valve trigger are provided which cyclically connect a vacuum and a blower to a filter. The valve has a box with three openings. The first opening is connectable to the vacuum. The second opening is connectable to the blower. 5 The third opening is connectable to the filter. A gate within the box is adapted to be biased by the blower and the vacuum to close the first opening. The gate is held against the bias by the external trigger to close the second opening. The external trigger is intermittently operated and is adapted to intervally release the internal gate to the bias to close the first opening and open the second opening. The preferred 10 gate is a flapper hinged for angular motion between the first and second openings. The preferred trigger is a rotating cam with a follower fixed to the flapper. The cam operation is controlled by a timer. As the cam perimeter remains engaged with the follower, the flapper is held against the bias to close the second opening. An irregularity in the perimeter of the cam intermittently disengages the cam from the 15 follower and releases the flapper to the bias of the air flow, allowing the flapper to slam against and close the first opening and open the second opening. The blower is energized in response to the timer so that it operates only when the cam is rotating.

A plurality of valves can be combined with a single trigger in a system for 20 cyclically connecting a plurality of filters to the vacuum and the blower. In the preferred system, a plurality of cam followers are equally angularly displaced along the perimeter of a circular cam. The cam irregularity is shaped to release each gate for approximately 1/12 rotation of the cam and intervally releases the gates to the bias to sequentially close their first openings.

BRIEF DESCRIPTION OF THE DRAWINGS:

Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

5 Figure 1 is a mechanical schematic drawing of a three filter cleaning machine employing three back-flow valves and a single valve trigger;

 Figure 2 is a perspective assembly view of the back-flow valves and valve trigger of Figure 1;

10 Figure 3 is a perspective view of the assembled back-flow valve and valve trigger of Figure 1;

 Figure 4 is a perspective assembly view of a preferred embodiment of the valves of Figure 1;

 Figure 5 is a top perspective view of the assembled valve of Figure 4;

15 Figure 6 is a bottom perspective view of the assembled valve of Figure 4;
and

 Figure 7 is an electrical schematic drawing of the machine of Figure 1.

20 While the invention will be described in connection with a preferred embodiment, it will be understood that it is not intended to limit the invention to that embodiment. On the contrary, it is intended to cover all alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION:

Turning first to Figure 1, a three-filter cleaning machine employing three back-flow valves and a single valve trigger is illustrated. During normal operation, a vacuum source S connected through valve V1, V2 or V3 pulls air contaminated with undesirable particles into three filters F1, F2 and F3 which remove the undesirable particles. While most of the accumulated particles are discharged into a filter pan, some of the particles amass on and clog the filter walls, diminishing the efficiency of the system. For back-flow operation, a blower B is connected to push air through the valves V1, V2 and V3 to their respective filters F1, F2 and F3 to dislodge the clogging particles from the filter walls. Each of the valves V1, V2 and V3 has a gate G1, G2 and G3, respectively, which seals off flow from the blower B into the valves V1, V2 or V3 and permits the vacuum source S to draw contaminated air into the filters F1, F2 and F3 during the normal vacuuming process. The gates G1 and G2 and G3 are mechanically held in place against the bias created by the blower B and the vacuum source S during the normal vacuuming process by a trigger T. The trigger T cyclically sequentially releases the gates G1, G2 and G3 to the bias of the blower B and the vacuum source S to cause them to seal off the suction of the vacuum source S and allow air pushed by the blower B to blast into the filters F1, F2 and F3. The trigger T is external to the valves V1, V2 and V3. In switching to the back-flow process, the trigger T completely disengages mechanical connection to the gates G1, G2 and G3 so that the bias afforded by the blower B and vacuum source S causes the gates G1, G2 and G3 to rapidly slam from the vacuum to the back-flow condition.

Looking now at Figures 2 and 3, the valve deck 10 is illustrated in greater detail. Valves V1, V2 and V3 are mounted on a base 11. For the three-filter machine illustrated, the base 11 has three passages 12, 13 and 14 which are equidistantly spaced from a center point 15 on axes 16, 17 and 18 and are equally angularly displaced from each other. The filters F1, F2 and F3 are mounted below

the plate 11 and aligned with the passages 12, 13 and 14, respectively, as best seen in Figure 1. The valves V1, V2 and V3 are secured to the top face of the base 11 by mounting plates 21 which receive bolts 22 extending upwardly from the base 11.

5 The valves V1, V2 and V3 are illustrated in greater detail in Figures 4-6. The mounting plates 21 have openings 23 which align with the passages 12, 13 and 14 through the base 11. A hub 24 at the center of each opening 23 allows the filter F1, F2 or F3 to be engaged beneath its respective opening 23. Each of the valves V1, V2 and V3 has sidewalls 25, 26, 27 and 28 and a cover 29 which, in cooperation with the mounting plate 21, defines the valve box. Two of the walls 25 and 28 have ports 31 and 32. Adapters 33 and 34, respectively, are secured at the ports 31 and 32 to facilitate connection of system ducts, seen in Figure 1, to the valve box. As shown, the ports 31 and 32 are in adjacent orthogonal sidewalls 25 and 28. A clapper 35, such as an approximately square sheet of metal stock, has circular disks 36 and 37 of compressible material attached to its opposite faces. The adapters 33 and 34 have circumferences within the valve boxes to provide a suitable sealing surface and the disks 36 and 37 are sized and textured to cooperate with the adapters 33 and 34 to seal the passages 31 and 32. One edge of the clapper 35 abuts and is fixed to a shaft 38 which extends above and below the upper and lower edges of the clapper 35. A brass bushing 42 is fitted into an aperture 41 in the corner of the cover 29 at the junction point of the sidewalls 25 and 28. Another brass bushing 44 is fitted into another aperture 43 in the mounting plate 21 which is vertically aligned with the aperture 41 in the cover 29. The upper and lower ends of the flapper shaft 38 are journaled for rotation in the bushings 42 and 44 so that the flapper 35 can rotate between a first position in which one of the disks 36 seals one of the ports 31 and a second position in which the other of the disks 37 seals the other of the ports 32. The upper end 45 of the shaft 38 further extends through its bushing 42 upwardly beyond the top of the cover 29 for

engagement with one end of a follower arm 46. The arm 46 is secured proximate one of its ends to the top end of the shaft 45. A threaded screw 47 through a split in the arm 46 tightens the aperture 48 into which the end 45 of the shaft is inserted. The arm 46 extends radially outwardly from the shaft 38 to a cam follower 51 which is journaled for rotation using a washer 52 on a post 53 extending upwardly from the arm 46. The seams of the valve box are sealed with a suitable duct sealant to insure the pneumatic integrity of the valves V1, V2 and V3.

Returning to Figures 2 and 3, a motor 54 is mounted beneath a motor mounting plate 55 with the shaft 56 of the motor 54 extending upwardly through the mounting plate 56. The bottom face of the motor mounting plate 56 is fastened to the top faces of the valve covers 29 with the axis 57 of the motor shaft 56 in vertical alignment through the center point 15 of the symmetrical arrangement of valves V1, V2 and V3. A circular cam 58 is concentrically mounted on the top of the motor shaft 56 by the cam hub 59. The diameter of the cam 58 is such that its circumference engages the cam followers 51 to hold the flapper disks 36 against the valve ports 31. This can be assured by adjustment of the angular position of the follower arms 46 in the gate shafts 38. An irregularity 61 in the circumference of the cam 58 completely disengages the cam 58 from mechanical contact with the follower 51 so that, when the follower 51 is released, its corresponding flapper 35 is free to rotate on its shaft 38 until the other disk 37 on the flapper 35 seals the other port 32 of its respective valve V1, V2 or V3. Looking at Figures 1, 2 and 3, a manifold 62 has outlets 63 connected by ducts 64 to their respective inlet ports 33 in the valves V1, V2 and V3. The blower B is connected by a duct 65 to the inlet of the manifold 62. Similarly, the vacuum source S is connected to the ports 32 of the valves V1, V2 and V3 by ducts 66.

Looking at Figures 1 and 7, the operation of the machine can be understood. The cam drive motor 54 is controlled through a switch 67 and time delay circuit 68 which are part of the trigger T. The cam 58 is normally engaged with the cam

followers 51 so as to hold the flappers 35 with their disks 36 sealing the blower inlet ports 31 into the valves V1, V2 and V3. In this position, the suction of the vacuum source S and the pressure from the blower B, the former drawing against the vacuum side disks 37 and the latter pushing against the blower side disks 36, biases the flappers 35 to rotate from the blower inlet ports 31 toward the vacuum outlet ports 32. However, the flappers 35 are held against the bias by the mechanical engagement of the cam 58 with the followers 51. As the cam motor 54 rotates the cam 58, the irregularity 61 in the cam circumference sequentially releases the cam followers 51 completely from mechanical engagement so that the gates G1, G2 and G3 are free to rotate in response to the bias to open the blower inlet ports 31 and slam the vacuum outlet ports 32 closed. Thus, air is no longer drawn by the vacuum source S into the filter F1, F2 or F3 associated with the released gate G1, G2 or G3 in the forward flow direction 71 but air is blown into the filter F1, F2 or F3 in reverse-flow direction 72 to dislodge particles collected on the filter walls during the vacuuming process. The contour of the irregularity 61 of the cam 58 is selected so as to release each cam follower 51 from mechanical engagement for approximately 1/12 of a rotation of the cam 58. Because of the rapid response of the mechanically released gates G1, G2 and G3, each filter F1, F2 and F3 experiences back flow for only 1/12 of a cam rotation and the entire system is experiencing back flow for only 1/4 of a cam rotation. Thus, even during the back flow process, the normal vacuum process continues at 100% effectiveness for 3/4 of the cam rotation. Furthermore, the timer rheostat 68A can be adjusted by the machine operator to cause its switch 68A to operate at any desired interval, preferably in a range of from 1.5 to 30 minutes. When the switch 67 is closed, a first relay 81 is energized, closing its normally open contacts 81A to energize the vacuum source S. The timer 68 is energized simultaneously through normally closed contacts 84A. As long as the timer 68 is energized, it will cause its switch 68B to operate at the intervals set by the timer rheostat 68A. Assuming, for

example, a selected interval of twenty minutes, the timer switch 6B will close twenty minutes after the switch 67 is turned "ON" and every twenty minutes thereafter. This will energize a second relay 83 which closes two of its normally open contacts 83A and 83B to engage the blower B and the cam motor 54, respectively, and third normally open contacts 83C in the circuit of a third relay 84. The third relay 84 controls the normally closed contacts 84A which control the timer 68. The energized cam motor 54 causes the cam 58 to rotate. A post 85A fixed to and rotating with the cam 58 activates a proximity switch 85 in the circuit of the third relay 84. The proximity switch is normally open. If the blower B and cam motor 54 are energized, the second relay contacts 83C are closed. When the proximity switch 85 closes, the third relay 84 opens the contacts 84A to de-energize the timer 68, opening the timer switch 68B and de-energizing the second relay 83 to shut off the blower B and cam motor 54 and reset the system which will repeat itself when the selected time interval of twenty minutes has elapsed. The proximity switch 85 is operated after one revolution of the cam 58. Therefore, each of the filters F1, F2 and F3 will receive one blast of blower air every twenty minutes and the blower B and cam motor 54 are energized for only one rotation of the cam 58 every twenty minutes. If, for example, the cam motor 64 drives the cam 58 at one (1) rpm, the back-flow process is in operation for only 1/20 of the vacuuming process and each filter will sequentially receive one five second blast of blower air during the one minute back-flow interval. In this manner, the back-flow process can be used to eliminate down time to replace or clean filters without any significant reduction in the power and efficiency of the vacuum process, even while back-flow is occurring. While the invention has been described in relation to a three-valve system, any number of valves and filters can be used applying the principles of the invention.

Thus, it is apparent that there has been provided, in accordance with the invention, a back flow valve and valve trigger for a cleaning machine that fully satisfies the objects, aims and advantages set forth above. While the invention has

been described in conjunction with a specific embodiment thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art and in light of the foregoing description. Accordingly, it is intended to embrace all such alternatives, modifications and variations as fall within the spirit of the appended claims.

5

Year	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	